

: www.eagleeyescctv.com/video : www.eagleeyescctv.com/facebook

AVM457A 2 Megapixel **IR Network Camera**



FEATURES

- Easy network setup with your iPhone / iPad
- POE (Power-over-Ethernet) support to eliminate the use of power cables and reduce installation costs
- **ONVIF** standard supported to simplify system integration
- External alarm I/O device connection
- IR LED built-in for night surveillance with effective range up to 20 meters
- **Remote Surveillance**
 - -- Fully compatible with iOS and Android devices, and Internet Explorer on Windows operating system
 - -- Push Video available on your iOS and Android devices when used with Push Video NVR series.

SPECIFICATIONS

■ Network		
Network Compression	H.264 / MPEG4 / MJPEG	
Multiple Video Streaming (Encode Modes, IPS, Resolution)	YES	
LAN Port	YES	
LAN Speed	10/100 Based-T Ethernet	
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP, RTCP,IPv4, Bonjour, UPnP, DNS,UDP,IGMP, QoS	
ONVIF Compatible	YES (Profile S)	
Frame Rate	30fps	
Number of Online Users	10	
Security	(1) Multiple user access levels with password(2) IP address filtering(3) Digest authentication	
Remote Access	(1) Internet Explorer on Windows operating system(2) 16CH Video Viewer on Windows & MAC operating system(3) EagleEyes on iPhone, iPad & Android mobile devices	
■ Camera		
Image Sensor	1/2.9" SONY CMOS image sensor	
Video Resolution	1080P to QVGA	
Min Illumination	0.1 Lux / F1.5, 0 Lux (LED ON)	
Shutter Speed	1/2 to 1/10,000 sec	
S/N Ratio	More than 48dB (AGC off)	





SPECIFICATIONS (Continued)

■ Camera		
Lens	f3.8mm / F1.5	
Viewing Angle	73.2°(Horizontal) / 47.4°(Vertical) / 85.4°(Diagonal)	
IR LED	35 Uints	
IR Effective Range	Up to 20 meters	
IR Shift	YES	
White Balance	ATW	
AGC	Auto	
IRIS Mode	AES	
POE	YES (IEEE 802.3af)	
External Alarm I/O	YES	
IP Rating	IP67	
Power Source (±10%)	12V / 1A	
Operating Temperature	-20℃~40℃	
Power Consumption (±10%)	7.1W (PoE); 7.1W (PoN); 6W (DC Adapter)	
■ Others		
Mobile Surveillance	iPad / iPhone / Android mobile device	
Motion Detection	YES	
Event Notification	FTP / Email / SMS	
RTC (real-time clock)	YES	
Digital Pan / Tilt / Zoom	YES	
Minimum Web Browsing Requirements	 Pentium 4 CPU 1.3 GHz or higher, or equivalent AMD 256 MB RAM AGP graphics card, Direct Draw, 32MB RAM Windows 7, Vista & XP, DirectX 9.0 or later Internet Explorer 7.x or later 	

^{*}The specifications are subject to change without notice



Official Website : www.eagleeyescctv.com : www.eagleeyescctv.com/video : www.eagleeyescctv.com/facebook

DIMENSIONS

Dimensional tolerance: ± 5mm





